


CPD12

1.2 Ton Counterbalanced Electric Stacker

LIFTING HEIGHT: 1400-4500MM

Load Curve



Advantages

Configuration and Performance

- Electronic power steering system, light and low noise.
- Two-way magnetic valve, three drop speed mode.
- AC Driving system, No carbon brush, maintenance free.
- Electromagnetic, regenerative braking system.
- Automatic lifting limit, proximity switch, long life.

Safety

- Curve automatic deceleration devices, more safe.
- Vehicle decelerates automatically at higher position.
- Stepless speed control system, safe and quiet.
- Controller with Multiple automatic protection.
- Emergency reversing device/Emergency brake switch.
- High position automatic reduction device.



AC | EPS

Free-maintained battery


Options fork tilt device

Counter-balanced electric stacker

Type	Lift height (mm)	Mast type	Option
CPD12-970	1400/2000/2500/3000/3300/3600	Standard 2-STAGE	TILTING DEVICE
CPD12-910	2500/3000/3300	FULL FREE 2-STAGE	-

Feature			
Model		CPD12	CPD12
Configuration No.		970	910
Type		Counterbalanced	
Mast type		Standard 2-Stage	Full free 2-Stage
Load capacity	kg	1200	1200
Load center	mm	500	500
Wheel base	mm	1179	1179
Operating type		Walkie/Stand On	
Wheels			
Wheels type		PU	PU
Wheel quantity Driving wheel/ Balance wheel/Bearing wheel		1/0/2	1/0/2
Dimension			
Standard lift height	mm	1400/2000/2500/ 3000/3300/3600	2500/3000/3300
Lowered fork height	mm	55	55
Fork size(length/width/thickness)	mm	1070/100/40	1070/100/40
Overall length	mm	2502/3012	2502/3012
Overall width	mm	1015	1015
Max.extend height	mm	2500/3100/3600/ 4100/4400/4700	3150/3650/3900
Mast lowered height	mm	1230/1580/1780/ 2030/2130/2300	1830/2080/2180
Min.Turning radius	mm	1352/1852	1352/1852
Min.Aisle width for pallets 800×1200	mm	2685/3175	2685/3175
Min.Aisle width for pallets 1000×1200	mm	2715/3195	2715/3195
Min.ground clearance	mm	80	80
Performance			
Travel speed,laden/unladen	km/h	5/5	5/5
Lift speed,laden/unladen	mm/s	130/180	130/180
Lowering speed,laden/unladen	mm/s	100/200	100/150
Gradeability,laden/unladen	%	5/7	5/7
Electrical configuration			
Drive motor/Lift motor/Steering motor	kW	AC1.5/DC3/DC0.15	AC1.5/DC3/DC0.15
Battery voltage	V	24	24
Battery capacity	Ah	270	270
Brake		Electromagnetic/Regenerative	
Controller		ZAPI (Options CURTIS)	
Weight			
Battery weight	kg	247	247
Service weight with battery	kg	1765	1921

* Details of specifications and equipment are based on information available at time of printing and may change without notice.



ANHUI HELI CO., LTD.

ADD: NO.668 Fangxing Street, Economical Development Zone, Hefei, P.R.China
 TEL: (86 551)63639068 (America) 63639258 (Europe) 63639358 (Asia)
 63662105 (Africa & Middle East) 63639530 (Key Accounts division)
 63662105 (Wheel loader)
 FAX: (86 551)63639966
 WEBSITE: <http://www.heliforklift.net>
 Email: heli@helichina.net

AUTHORIZED DEALER