

CBD15-170J

Electric Walkie Pallet Truck

Advantages

Configuration and Performance

- The truck has compact structure and is economic.
- Permanent magnet drive motor assembled on the truck has simple structure and is easy for maintenance.
- Stepless speed regulating is easy for operation and maintenance.
- Open type layout of battery is easy for replacement.
- Built-in charger is standard configuration.
- Maintenance-free battery is safe and non-pollution.
- The truck is compact and suitable for narrow space operation.
- Special design for Fork in and out of double-faced pallet.
- Lifting automatic limit is safe and energy saving.
- Emergency reversing device and emergency brake switch are standard configuration.
- The truck has low noise and small energy consumption and only 2 kw/h energy is consumed daily.



HELI CBD15-170J

| Feature | | | |
|--------------------------------------------|------|--|-----------------------------------------------------------------|
| Model | | | CBD15 |
| Configuration No. | | | 170J |
| Weight | | | 1500 |
| Load center | kg | | 600 |
| Wheel base | mm | | 1285/1235 |
| Operating type | mm | | Walkie |
| Wheels | | | |
| Wheels type | | | PU |
| Wheel quantity | | | 1/0/4 |
| Driving wheel/Balance wheel /Bearing wheel | | | φ210×70 |
| Driving wheel size | mm | | φ84×70 (双) |
| Balance wheel size | mm | | φ80×101 (单) |
| Bearing wheel size | mm | | — |
| Dimension | | | |
| Min.fork lowered height | mm | | 85 |
| Max.fork lifting height | mm | | 205 |
| Max.lifting height | mm | | 120 |
| Outside width between forks | mm | | 550/685 |
| Inside width between forks | mm | | 390 |
| Fork length | mm | | 1150/1200 |
| Fork width | mm | | 160 |
| Fork thickness | mm | | 73 |
| Overall length | mm | | 1648/1698 |
| Overall width | mm | | 570/685 |
| Overall height(With handle) | mm | | 1213 |
| Overall height(Without handle) | mm | | 634 |
| Min.Turning radius | mm | | 1414/1464 |
| Min.Aisle width for pallets 800×1200 | mm | | 1728/1778 |
| Min.Aisle width for pallets 1000×1200 | mm | | 1764/1814 |
| Performance | | | |
| Travel speed,laden/unladen | km/h | | 3.5/4 |
| Lift speed,laden/unladen | mm/s | | 30/35 |
| Lowering speed,laden/unladen | mm/s | | 35/30 |
| Gradeability,laden/unladen | % | | 5/7 |
| Electrical configuration | | | |
| Drive motor | KW | | DC0.65 |
| Lift motor | KW | | DC0.8 |
| Steering motor | KW | | — |
| Battery voltage / capacity | V/Ah | | 24/75(Standard)/85(Options) |
| Brake | | | Electromagnetic/regenerative |
| Controller | | | Standard configuration HELI/Optional configuration CURTIS 1212F |
| Weight | | | |
| Battery weight | kg | | 50 |
| Service weight with battery | kg | | 210 |

* Details of specifications and equipment are based on information available at time of printing and may change without notice.



ANHUI HELI CO., LTD.

ADD: NO.668 Fangxing Street,Economical Development Zone,Hefei,P.R.China
TEL : 63639068(America); 63639258(Europe); 63639358(Asia); 63662105(Africa & Middle East);
63639530(Warehouse Equipment); 63639531(Wheel loader)
FAX : (86 551)63639966
WEBSITE : <http://www.helichina.net>
Email : hel@helichina.net

AUTHORIZED DEALER